NRL Report 8143

Complex Cepstrum Processing
of Digitized Transient Calibration Data
for Removal of Echoes

L. B. POCHÉ, JR.

Methods Section
Underwater Sound Reference Division

September 30, 1977

NAVAL RESEARCH LABORATORY
Washington, D.C.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NRL Report 8143	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) COMPLEX CEPSTRUM PROCESSING OF DIGITIZED TRANSIENT CALIBRATION DATA FOR REMOVAL OF ECHOES		5. TYPE OF REPORT & PERIOD COVERED Interim report on a continuing NRL Problem.
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Lynn B. Poche, Jr		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Underwater Sound Reference Division Naval Research Laboratory P. O. Box 8337, Orlando, FL 32806		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Problem No.: S02-42.201 PE: 62711N Proj: XF 11-121-200
11. CONTROLLING OFFICE NAME AND ADDRESS Department of the Navy Naval Electronics Systems Command Washington, D. C. 20360		12. REPORT DATE September 30, 1977
		13. NUMBER OF PAGES 29
14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Complex cepstrum
Deconvolution
Echo reduction
Low-frequency calibration

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

The complex cepstrum technique was investigated for possible use in removing echoes caused by early reflections when low-frequency, peaked-response transducers are calibrated with transient signals. The calibration environment permits a high signal-to-noise ratio and a free choice of input waveforms, both of which are advantages in complex cepstrum processing. The proper method of computation with this technique is discussed in detail. Cepstrum filtering methods are discussed. Synthetic measurement
(Continued)

DD FORM 1473 EDITION OF 1 NOV 65 IS OBSOLETE
1 JAN 73
S/N 0102-LF-014-6601

20. ABSTRACT (Continued)

data produced by a J9 projector driven with a damped sinusoidal pulse and a pressure-release reflection are shown, and real measurement data from a low-frequency line array driven by a single-cycle sinusoid with complex surface and bottom reflections are also shown. In both the synthetic and the real data, the echoes were successfully removed using the complex cepstrum technique. Data were digitized directly and stored on digital magnetic tape. Oversampling was reduced by sifting to achieve the correct sampling rate required by the complex cepstrum method. The results indicate that echo removal performed by complex cepstrum processing can be accurate enough to have potential usefulness in calibration procedures.

CONTENTS

COMPLEX CEPSTRUM PROCESSING OF DIGITIZED TRANSIENT CALIBRATION DATA FOR REMOVAL OF ECHOES

INTRODUCTION

Calibration procedures employing broadband transient signals have been under development for several years at the Underwater Sound Reference Division (USRD) of the Naval Research Laboratory. The principal advantages of the broadband transient system [1] over conventional continuous wave (CW) sweep-frequency or pulsed systems appear to be reduced calibration time and convenience in obtaining the complex receiving response of a hydrophone. Reflections from within the boundaries of the calibration medium interfere with observation of the received waveform, thus limiting the available processing time per pulse and hence the frequency resolution of the resulting calibration. In calibration of certain low-frequency, peaked-response transducers, this problem can impose extreme limitations. The transfer function of the calibration enclosure (which is taken here to include such bodies of water as lakes or pools as well as tanks) distorts the direct-arrival part of the signal through the process of convolution. It follows that the true direct-arrival part of the signal must be recovered by deconvolution. The calibration environment permits a high signal-to-noise ratio and a free choice of input waveforms. These two advantages greatly increase the prospects for success of the deconvolution method under study here.

Systems or classes of signal-processing techniques that obey a generalized principle of superposition have been called homomorphic. A well-known homomorphic system for deconvolution developed by Schafer [2] employs the complex cepstrum. Ulrych [3] gives an excellent summary of the theory of this system; however, his examples are somewhat confusing.

The basic steps necessary in the complex cepstrum process are given in Fig. 1. (Complex cepstrum is the name given to one function in the train of operations, arrived at in the bottom of Fig. 1. We shall refer to that function, and sometimes to the entire system, as the cepstrum.) These steps will be discussed in greater detail later. Although the required steps appear to be easily implemented, satisfactory results may be difficult to obtain until certain details of the basic steps are carefully studied. One purpose of this report is to discuss in detail the computation method of this system. A second purpose is to demonstrate the proper procedure for applying the process to real data.

CEPSTRUM PROGRAM THEORY

A computer program that will accomplish the deconvolution by means of the complex cepstrum technique can be written by performing the steps called for in Fig. 1.

Step 1 consists of simply transforming the time series into the frequency domain by performing a fast Fourier transform (FFT) operation.

1

Fig. 1 — Steps in the complex
cepstrum process

Step 2, taking the complex logarithm, is done by employing the relation

$$\log z = \log r + i\theta$$

where $z = x + iy$. But r, the magnitude, equals $\sqrt{x^2 + y^2}$, and θ, the phase, equals $\tan^{-1}(y/x)$. Log r and θ become the real and imaginary components of a complex number representing the complex logarithm of z.

Steps 3 and 4 are called "unwrapping the phase." They are extremely critical steps in the process. In order to be able to identify the periodic component representing the echo in this sequence, it is necessary to remove the numerous discontinuities in the phase that arise from the multivalued definition of $\tan^{-1}$. Each time the phase value reaches $\pm\pi$, a discontinuity of 2π appears in the function. These discontinuities must be forced out of the function by adding or subtracting 2π to all subsequent values, as appropriate. This process is performed in the computer program be comparing each successive point to its neighbor. If a difference of 3 or more is found between neighboring values, the second point is identified as a positive or negative discontinuity, as the case may be, and an adjustment is made to this and all succeeding points. The value 3 was arrived at empirically. The sampling used causes the actual values obtained between discontinuous points to vary. If the frequency intervals are too coarse, discontinuities can even be lost. This can be avoided by sampling for a long enough time to provide adequate frequency resolution. If sufficient time or record length is not available, zeroes can be added to the time sequence as required. Because the phase data are always antisymmetric, we can generate the second half of the data by forming an inverted mirror image of the first half. Then we need only to phase-unwrap the first half.

2

Removal of the discontinuities introduces a huge linear slope, which is removed next, in step 4.

Improper or incomplete removal of the linear phase will leave large components in the cepstrum sequence, which mask the true amplitude of the echo impulse train components. The method we use to remove the linear phase may be explained by letting δT be the sampling interval and N be the total number of samples. We wish to eliminate any net time delay. If there is a delay of M samples, we wish to shift the data back by $M\delta T$. A time delay of $M\delta T$ shows up in the spectrum as a multiplicative factor of $\exp{(iM\delta T\omega)}$. In the phase of the spectrum (the imaginary part of the logarithm) it shows up as an additive term ϕ_d, where $\phi_d = M\delta T\omega$.

Now

$$\omega = n\delta\omega \qquad\qquad n = 0, 1, \ldots, \left(\frac{N}{2}\right)$$

and

$$\delta\omega = \frac{2\omega_{max}}{N}$$

where

$$\omega_{max} = \frac{\pi}{\delta T} \ .$$

So

$$\phi_d = \frac{2\pi M n}{N} \qquad\qquad n = 0, 1, \ldots, \left(\frac{N}{2} - 1\right) .$$

In this case, n ranges only to $(N/2 - 1)$ because the FFT requires that N be an even number. The phase function will have a point of symmetry at $N/2$, which has a value of zero. The total phase is then

$$\phi(n) = \phi_0(n) + \phi_d(n) \qquad n = 0, 1, \ldots, \left(\frac{N}{2} - 1\right)$$

By the integral definition of M, its value can be chosen such that the absolute value of $\phi_0(N/2)$ is always less than π. If N is large, $\phi(N/2)$ is approximately equal to $\phi_0(N/2 - 1)$. Then the total phase,

$$\phi\left(\frac{N}{2} - 1\right) \approx \phi_0\left(\frac{N}{2}\right) + \phi_d\left(\frac{N}{2} - 1\right) \approx \phi_0\left(\frac{N}{2}\right) \frac{2\pi M}{N}\left(\frac{N}{2} - 1\right) \approx \phi_0\left(\frac{N}{2}\right) + \pi M - 2\pi\frac{M}{N},$$

and

$$\frac{\phi\left(\frac{N}{2}-1\right)}{\pi} \approx M + \frac{\phi_0\left(\frac{N}{2}\right)}{\pi} - 2\frac{M}{N}$$

Again, if N is very large compared to M, the last term is negligible. We have seen that the second term must be less than 1. So M is the integer closest to $[(N/2) - 1]$. To form a rounded value, set M equal to the integer value

of

$$\frac{\phi\left(\frac{N}{2}-1\right)}{\pi} + 0.5 \quad \text{for positive } M$$

and

$$\frac{\phi\left(\frac{N}{2}-1\right)}{\pi} - 0.5 \quad \text{for negative } M.$$

Since $\phi_0(n) = \phi(n) - \phi_d(n)$, the corrected phase is given by

$$\phi_0(n) = \phi(n) - \left(\frac{\pi M}{\frac{N}{2}}\right) n.$$

(The term in brackets is the correction increment, FAZINC, used in the computer program given in the Appendix.)

Step 5, which follows, consists of performing the inverse transform by an FFT operation. This yields the complex cepstrum (which is actually a real function with no imaginary part, because the real part of the log spectrum is symmetric and the imaginary part is antisymmetric).

Step 6, called linear filter, may apply to any operation that is intended to separate the echo impulse train from the underlying cepstrum curve. In our case we wish to remove the echo. The simplest method might be to zero all values beyond a chosen point. That operation is called an early-pass filter, corresponding to the low-pass filter in the frequency domain. Because the cepstrum tends to concentrate the direct-arrival signal in the earliest part of the curve, most of that signal would be undisturbed by such an operation. The process's effectiveness depends mostly on how well the direct-arrival and echo portions of the cepstrum can be separated. This in turn depends on how close in time the echo and direct signal are.

A more specific method of removing the echo would be to identify the individual points in the echo impulse train and set those to zero, leaving the intervening parts of the

direct-arrival cepstrum undisturbed. This operation is termed a comb filter. In practice, it allows removal of echo signals of shorter delay than the early-pass filter. But zeroing a sequence of points can produce a disturbance when the underlying cepstrum is non zero at those points. A better method would be to try to replace the sequence of points with values from an estimate of the echo-free cepstrum. In our observations of the cepstra of properly sampled, band-limited signals, the direct-arrival signal component seems to have an alternating-point structure which can be immediately visualized by referring to it as "Jaws." The best linear approximation for this type of structure cannot be made from adjacent points, but it can be made directly from the points two samples removed from the central point. Thus, if an echo impulse point to be removed is located at point K, the straight-line approximation between $K - 2$ and $K + 2$ is used to replace K. The algorithm also works well for smooth curves. A general expression to designate values of K is

$$K = M \times n + 1 \qquad n = 1, 2, 3, ..., \left(\frac{N}{M}\right)$$

where M is the delay interval between signal and echo in sample points and N equals the total number of sample points in the sequence. A second pass may be formed by

$$K = M \times n + 1 - N \qquad \left(\frac{N}{M}\right) < n < \left(\frac{2N}{M}\right).$$

In both cases n is always an integer.

Steps 7 through 10 are performed to reconstruct the time-series waveform with the echo removed. Step 7 transforms the sequence back into the frequency domain with an FFT operation. Next, in step 8, the linear phase component is restored using the same increment that was determined in step 4. In step 9 complex exponentiation is performed. This returns the spectrum to a linear state.

Between steps 1 and 2, the first term in the real part of the spectrum (the DC term) was tested for algebraic sign. This information was stored, and if that sign was found to be negative, the sign of the entire spectrum was reversed. The original sign is now restored just before step 10. Schafer [2] gives a good discussion of the reason for this operation.

Step 10 is an inverse FFT operation to return the sequence to the time domain. We now have the reconstructed time-series signal with echo removed.

With a computer program to perform these steps in hand, we tried removing echoes from some experimental data. The results were generally unacceptable. In order to discover where our problems were, we decided to apply the program to some more easily controlled synthetic data.

SAMPLING CONSIDERATIONS

The first data sequence used to test the cepstrum program was a simulated waveform generated from an analytic function and forced to appear much like the waveform used by Ulrych (Fig. 2). The data sequence is 128 samples long. An echo of 0.9 magnitude and delayed by 12 samples was then added, making the composite signal appear as in Fig. 3. The total wavelet occupies about 45 samples. After the first FFT (step 2), one thing immediately apparent about the simulation was the very narrow band-width of the spectrum. This result may be seen in Fig. 4, where the right half represents the negative-frequency part of the transform translated upwards (this is the appearance of normal output from an FFT routine). Because the energy in the high-frequency part of the spectrum approaches zero, the logarithm of the magnitude produces large negative values, and the phase curve becomes erratic. After considerable experimenting, we were able to keep these erroneous values from swamping the higher energy parts of the spectrum by introducing a small impulse, or "glitch," into the time series. Its echo was produced with the same amplitude and time delay as that of the data signal, the only intention being to supply some energy to the high-frequency parts of the spectrum. When the glitch is introduced, the real part of the complex logarithm appears as in Fig. 5. Note that the effects of the glitch and its echo are apparent in the high-frequency area. The results of phase-unwrapping are seen in Figs. 6 and 7. Figure 6 shows the imaginary part of the data. The discontinuities have been removed from the left half but not from the right. It was necessary to place the glitch at the center of the data impulse to avoid introducing into the imaginary part another phase component representing delay between the data impulse and the glitch. This phase component would appear as a different slope over the glitch-dominated frequencies in Fig. 6, producing a kink in the linear ramp. This double slope would prevent the linear phase from being minimized and cause masking of the impulse train in the cepstrum. The complete unwrapped phase signal appears in Fig. 7. There is a considerable difference in vertical scale from Fig. 6. The complex cepstrum is seen in Fig. 8.

The echo energy is represented by the alternating impulse train. The first spike in Fig. 8 is at the 13th sample, and succeeding spikes appear at each 12th sample following. The right half of Fig. 8 represents the same negative-frequency translation effect shown in Fig. 4, except that the diminishing impulse train does not belong in the negative-frequency region. Furthermore, if the vertical scale is changed to magnify the curve, it can be seen that the impulse train wraps around the cepstrum modulo 128.

The linear filter operation was performed using the special comb filter. The result of two passes of the filter, replacing every 12th point starting with 13 and then every 12th point starting with 5, is shown in Fig. 9. The result of the reconstructed time-series waveform is shown in Fig. 10.

We found no way to obtain the preceding result with this signal without resorting to the glitch while still maintaining the number of samples used. However, the problem posed by near-zero energy in the high-frequency part of the spectrum shown in Fig. 4 may be dealt with in a more satisfactory way. By sampling at or slightly below the Nyquist rate, we caused the important energy region to just fill the spectrum. This results in a very nice-looking cepstrum which, unfortunately, has an almost unrecognizable time-series waveform. The method is workable, however, and is the method used in the remaining examples.

6

Fig. 2 — Simulated waveform (128 samples)

Fig. 3 — Simulated waveform plus echo
Echo amplitude = 0.9
delay = 12 samples

Fig. 4 — Spectrum of simulated
waveform of Fig. 3

Fig. 5 — Real part complex logarithm of
simulated waveform plus "glitch"

Fig. 6 — Imaginary part corresponding to Fig. 5.
Left half: after removal of phase discontinuities,
right half: before removal of phase discontinuities.

Fig. 7 — "Phase unwrapped" imaginary part

7

Fig. 8 — Complex cepstrum of simulated waveform

Fig. 9 — Filtered cepstrum

Fig. 10 — Reconstructed simulated
waveform minus echo

Moreover, as will be discussed later, an oversampled waveform can always be generated from a properly sampled one.

Having successfully, if somewhat deviously, replicated the waveforms of Ulrych, we began to search for a better choice of driving signal. The problem was obviously with the sampling rate; and the solution was not to put a glitch in the signal, but to sample at exactly the right rate. One trial signal that seemed promising was the impulse response of an eight-pole Chebyshev filter. The idea here was to have a sharp high-frequency cutoff to avoid aliasing problems when the signal was sampled at exactly the correct rate. Figure 11 shows the Chebyshev filter impulse response as it would appear in an esthetically pleasing but oversampled form. In Fig. 12 we see the log spectrum derived from the oversampled signal. Note the sharp high-frequency cutoff and the undesirable low-amplitude, high-frequency components. Figure 13 shows the same waveform when the sampling rate has been changed to the proper value for cepstrum processing; Fig. 14 is the log spectrum, now showing only about 7-dB amplitude variation instead of 60 dB. Hardly any aliasing can be seen. In Fig. 15 an echo has been added to the waveform. This results in

8

a cepstrum (Fig. 16) which contains a very prominent sequence of single points representing the echo. This sequence of points was removed by using the special comb filter, and the reconstructed signal is shown in Fig. 17. A careful comparison of Fig. 17 and Fig. 13 shows that the two are virtually identical.

When employing artificially generated signals as input sequences in this manner, there is a normal tendency to form the time-series waveform by adding to the original signal a reduced-amplitude replica delayed by some integral number of sample points. In actual practice, the echo will seldom be delayed by an exact number of samples. The peak of the echo impulse might just as well fall midway between two sample points. In order to investigate the effect of this placement of echoes on the cepstrum, we included in the original synthesizing program a provision for making the echo delay continuously variable between sample points. Figure 18 shows the cepstrum that results when the echo is introduced midway between sample points. Comparing this figure with the integral sample delay version (Fig. 16), we see that the impulse train peaks have been reduced in amplitude and spread so that they are no longer single points. An attempt to remove the echo represented in Fig. 18 by the comb filter is generally unsuccessful, even with repeated passes, as can be seen from Fig. 19.

At this point it is clear that there are two rules pertaining to sampling that must be observed. First, the signal must be sampled at exactly the proper rate: a rate low enough that the spectrum does not extend beyond the frequencies of interest, and high enough that no significant aliasing takes place. Second, the samples must be chosen so that the echo falls on or very nearly on a sample point. The technique we used to accomplish this was to sample at as high a rate as possible consistent with the other requirements of the system (for example, storage). To obtain the desired sampling rate, we would sift the data, saving every Pth point, where P represents the divisor necessary to give proper sampling, and then shift the starting point of the sequence until the echo fell as close as possible to a sample point. With this technique we were able to obtain good results from our records of real experimental data.

|	
0.00 140.00	0.00 140.00
Fig. 11 — Impulse response of eight-pole Chebyshev filter	Fig. 12 — Log spectrum of Chebyshev filter

9

Fig. 13 — Properly sampled Chebyshev filter impulse response without echo


Fig. 14 — Log spectrum of properly sampled waveform



Fig. 15 — Waveform with echo added

Fig. 16 — Complex cepstrum of signal plus echo

Fig. 17 — Reconstructed waveform with echo removed

Fig. 18 — Cepstrum of signal with echo delayed midway between samples

10

Fig. 19 — Reconstructed waveform, mid-sample echo

EXPERIMENT

In order to test the program with the real experimental data, we used two types of signals that had been recorded previously. One type of waveform was obtained by using a damped sinusoid as the driving current, and the other type by using a single-cycle sine wave. The first was produced by driving a J9 transducer with a damped sinusoidal waveform and detecting with an H52 hydrophone. A reflector, consisting of a large, square piece of closed-cell neoprene cemented to a 1/4-in.-thick plexiglass plate, had been positioned so as to supply an echo with adjustable delay. The hydrophone signal was directly digitized using a Nicolet digital oscilloscope and recorded on a digital tape unit. The digitizing rate was set at the highest value that would allow the entire signal waveform to be stored within the 4096-point capacity of the oscilloscope. Results of two of these experiments are shown in Figs. 20 through 27. The original impulses with no echoes are reproduced graphically in Figs. 20 and 24. These waveforms were obtained by removing the reflector plate from the water. Next, the reflector was lowered to contribute the echo (Figs. 21 and 25). The driving waveform in the first four figures (Figs. 20-23) was a damped, ringing impulse from an RLC circuit. In the second set of figures (Figs. 24-27), the circuit was adjusted to give a much longer time constant, so that only the first half-cycle is seen here. The early part of the impulse is due to the transient response of the J9 transducer. Figures 22 and 26 show the cepstrum resulting from each waveform. Note that in the case of a pressure-release echo, the echo appears in the cepstrum as a sequence of negative impulses only, instead of as an alternating sequence. The same comb filter that was used previously has been applied; the reconstructed results are shown in Figs. 23 and 27.

Another type of data used was a sample of actual transient calibration data from an element of a line array hydrophone. The data were recorded at our Leesburg Facility. Rigging is usually done there at a depth where the pressure-release surface reflection will arrive at approximately the same time as the hard reflection from the side walls of the

11

L. B. POCHE, JR.

spring. In the case of omnidirectional instruments this results in a minimum amplitude but somewhat distorted echo. Figures 28 and 29 show the received waveform in the over-sampled and properly sampled forms, respectively. Bearing in mind the distorted form of the echo, we were not surprised to see the clearly unspectacular cepstrum as it appears in Fig. 30. What is surprising is the degree to which the echo is eliminated with a single pass of the comb filter (Fig. 31).

Fig. 20 — Experimental waveform from
J9 transducer

Fig. 21 — Experimental waveform with echo

Fig. 22 — Complex cepstrum of
signal plus echo

Fig. 23 — Reconstructed waveform
with echo removed

12

Fig. 24 — Experimental waveform from
J9 transducer

Fig. 25 — Experimental waveform with echo

Fig. 26 — Complex cepstrum of
signal plus echo

Fig. 27 — Reconstructed waveform with
echo removed

Fig. 28 — Transient calibration signal
with echo, oversampled

Fig. 29 — Signal plus echo,
properly sampled

Fig. 30 — Complex cepstrum of transient
calibration signal

Fig. 31 — Reconstructed signal with
echo removed

In all of the previous examples, the properly sampled input signals and the reconstructed versions have a spiky appearance, which makes them difficult to relate to the oversampled data we are accustomed to seeing. It is desirable to restore the smoothed appearance to the sampled signal by interpolation. The interpolation formula used was derived from the expression:

$$x(t) = \sum_{n = -\infty}^{\infty} x(nT) \frac{\sin 2\pi f_c(t - nT)}{2\pi f_c (t - nT)}$$

which assumes that the signal $x(t)$ is band-limited and the spectrum is zero for $|f| > f_c$ and $T = 1/(2f_c)$. If interpolation points are chosen midway between sample points, the computation is reduced to

$$x[(m + 1/2)T] = \sum_{n = 0}^{N} x(nT) \frac{(-1)^{m + n}}{\pi(m + 1/2 - n)} .$$

The process of interpolating midpoints is repeated until the entire array of 512 points is filled. Figures 32 and 33 illustrate the results obtained using the modified program on the data of Figs. 29 and 31, respectively.

Up to now we have only briefly mentioned other obvious methods of linear filtering for the cepstrum (e.g., "late-pass" and "early-pass" filtering). These are analogous to high-pass and low-pass in the frequency domain. In our case, a high signal-to-noise ratio and the ability to select an optimum driving signal make it possible to keep the cepstrum "clean" enough for the echo impulse train to be identified clearly. When the source signal and the echo are closely spaced in time, the signal portion of the cepstrum and the

14

impulse train may not be separated enough to avoid producing severe distortion in the source signal when early-pass filtering is used. Stated another way, it appears that the co.. h filter is able to remove echoes that have a shorter delay time than those the early-pass li... ...move. Early-pass filtering can be useful in cases where the echo does not ap-p... ... ...m as a sequence of single points, either because of distortion or because t.. ... ...etween sample points, as in Fig. 18. Late-pass filtering is of limited use-ful. ... ...e result of reconstruction indicates the time delay, which should be de-tec.a.e ... ..pstrum as well.

Fig. 32 — Transient calibration data with echo, properly sampled, smoothed

Fig. 33 — Reconstructed signal, echo removed, smoothed

Exponential weighting, as discussed in Ulrych [3] and elsewhere, has not been mentioned in the above discussion. The cepstrum method does not work at all if the echo sequence is not minimum phase (see Schafer [2]). Exponential weighting can be useful in forcing the echo components to be minimum phase, should there be multiple echoes. Too much weighting can cause considerable inaccuracies in recovering the source signal, however. The effect of exponential weighting is chiefly of use when it is more important to detect the delay time than to recover the source signal.

CONCLUSION

We have demonstrated that echo removal performed by complex cepstrum processing can be accurate enough to have potential usefulness in calibration procedures.

ACKNOWLEDGMENTS

15

REFERENCES

1. A. Z. Robinson and L. G. Beatty, "The Use of Broadband Signals for Underwater Acoustic Transducer Calibration," NRL Report 7883, Apr. 17, 1975.

2. R. W. Schafer, "Echo Removal by Discrete Generalized Linear Filtering," Ph.D Thesis, Dept. of Elec. Engr., MIT, Feb. 1968, Sec. 2.9, p. 69.

3. T. J. Ulrych, "Application of Homomorphic Deconvolution to Seismology," *Geophys.* **36** (No. 4), 650-660 (Aug. 1971).

Appendix A
COMPUTER PROGRAMS AND SUBROUTINES

This section contains listings of the computer program and subroutines pertinent to this report. The source language is Fortran IV, and all programs were implemented on a Digital Equipment PDP-11/45 computer with a multi-user operating system. Subroutines that have not been listed either are specific to the operational details of our system and, as such, would be of little use to others, or are ordinary utility subroutines that probably already exist in a prospective user's library. In those cases, a full explanation of the functional nature of each subroutine is given.

```
FORTRAN IV-PLUS V02-04          16:43:15    19-JAN-77          PAGE 1
PPTEST.FTN          /RO/TR:BLOCKS/WR
          C   ---PROGRAM PPTEST(3)              3 JAN 77
          C
          C
          C   ---THIS VERSION USES SINGLE PRECISION FOR
          C
          C              *** EVERYTHING ***
          C
          C         USES NO COMPLEX FUNCTIONS
          C
          C
          C
          C
0001              DIMENSION IHEAD(3),IRAY(200),JRAY(200),FAKIT(1024)
0002              BYTE ILFA(30),FILT
0003              PI=3.14159265
          C             THIS CALL SUPPRESSES FLOATING ZERO DIV ERROR*
0004              CALL ERRSET(73,.TRUE.,.FALSE.,.FALSE.,.FALSE.,)
          C                OPTIONAL SUBROUTINE SUBSTITUTES ANALYTICALLY GENERATED
          C                SIMULATED WAVEFORM(AFTER ULRYCH) FOR REAL DATA.
0005              WRITE(6,462)
0006              READ(5,463)IULRY
0007              IF(IULRY.EQ.1)N=128
0008              IF(IULRY.EQ.1)GO TO 4
          C             SPECIFY INPUT FILE*
0009              WRITE(6,20)
0010              READ(5,30)ICNT,ILFA
0011              ILFA(ICNT+1)=0
          C             SET UP FILENAME ARRAY FOR INPUT FILE, SPECIFY # OF PTS
          C             TO READ FROM FILE.
0012              WRITE(6,142)
0013              READ(5,109)NF
          C             SPECIFY NO OF DATA ARRAY POINTS (UP TO 512). MUST BE
          C             A POWER OF 2.
0014              WRITE(6,106)
0015              READ(5,109)N
0016      4       IHN=N*2
0017              SN=FLOAT(N)
0018              QN=FLOAT(IHN)
          C             CHOOSE COMB,EARLY PASS OR LATE PASS GATING TO BE DONE
          C             ON CEPSTRUM
0019              WRITE(6,11)
0020              READ(5,34)FILT
0021              IF(IULRY.EQ.1)CALL UF(FAKIT)
0022              IF(IULRY.EQ.1)GO TO 3
          C             CALL THE INPUT SIGNAL FILE-READING SUBROUTINE. THIS SUBR.
          C             ALLOWS VARIABLE STARTING POINT 8 SIFTING FACTOR,
          C             LOADS DATA IN ARRAY.
0023              CALL FILRED(FAKIT,ILFA,NF)
          C             SELECT OPTION TO BYPASS PROGRAM. GOES TO DIRECT
          C             INTERPOLATION OF SIFTED INPUT DATA
0024              WRITE(6,230)
0025              READ(5,463)IORIG
0026              IF(IORIG.EQ.1)GO TO 250
0027      462     FORMAT('$ IF YOU WANT ULRYCH TYPE 1: ')
0028      463     FORMAT(I50)
          C             OUTPUT A FILE FOR PLOTTING THE RAW DATA
```

```
FORTRAN IV-PLUS V02-04          16:43:15      19-JAN-77            PAGE 2
PPTEST.FTN              /RO/TR:BLOCKS/WR
0029    3       CALL PLTFIL(FAKIT,0,N,1)
        C               OPTION TO USE EXPONENTIAL WEIGHTING
        C               IF EXP.WEIGHTING IS USED,SPECIFY EXP.,IF NOT,INPUT 1
0030            WRITE(6,119)
0031            READ(5,112)GAM
0032            IF(GAM.EQ.1.E0)GO TO 21
0033            FAM=1.E0/GAM
0034            DO 1 I=1,IHN,2
0035            FAM=FAM*GAM
0036            FAKIT(I)=FAKIT(I)*FAM
0037    1       CONTINUE
0038    10      FORMAT(2F9.4)
        C               TRANSFORM TO FREQ DOMAIN
0039    21      CALL FFTDP(FAKIT,N,-1)
        C               TRAP TO INVERT SPECTRUM IF DC COMPONENT IS NEGATIVE.
0040            FAKSIG=FAKIT(1)/ABS(FAKIT(1))
0041            DO 350 I=1,IHN
0042            FAKIT(I)=FAKIT(I)*FAKSIG
0043    350     CONTINUE
        C               OUTPUT A FILE FOR PLOTTING THE SPECTRUM DATA.
0044            CALL PLTFIL(FAKIT,0,N,1)
        C               TAKE COMPLEX LOG OF SPECTRUM-THE HARD WAY.
0045            DO 54 I=1,IHN,2
0046            DBAS=SQRT(FAKIT(I)*FAKIT(I)+FAKIT(I+1)*FAKIT(I+1))
0047            DANG=ATAN2(FAKIT(I+1),FAKIT(I))
0048            DOLG=ALOG(DBAS)
0049            FAKIT(I)=DOLG
0050            FAKIT(I+1)=DANG
0051    54      CONTINUE
        C               OUTPUT A FILE FOR PLOTTING THE LOG SPECTRUM DATA.
0052            CALL PLTFIL(FAKIT,0,N,1)
0053            MP=0
0054            NP=0
        C               UNWRAP THE PHASE
        C               LOOK FOR DISCONTINUITIES
        C               AND COUNT POS 8 NEG ONES SEPARATELY
        C               START @ IMAG.PART OF 2ND PT, COMPARE IT TO 1ST PT. GO
        C               TO MIDPT.,IF DIFFERENCE IS =>3,IT'S A DISCONTINUITY
0055            DO 51 I=4,N+2,2
0056            FAZDIF=FAKIT(I)-FAKIT(I-2)
0057            IF(ABS(FAZDIF)-3.E0)51,41,41
0058    41      IF(FAZDIF)42,999,43
0059    43      NP=NP+1
0060            IRAY(NP)=I
0061            GO TO 51
0062    42      MP=MP+1
0063            JRAY(MP)=I
0064    51      CONTINUE
0065            IRAY(NP+1)=N+4
0066            JRAY(MP+1)=N+4
0067            TDELT=0.E0
0068            PDELT=0.E0
0069            IF(NP.EQ.0)GO TO 305
        C               UNWRAP THE POS DISCS
0070            DO 301 I=1,NP
0071            PDELT=PDELT+2.E0*PI
```

A3

```
FORTRAN IV-PLUS V02-04          16:43:15   19-JAN-77           PAGE 3
PPTEST.FTN          /RO/TR:BLOCKS/WR
0072                DO 302 J=IRAY(I),IRAY(I+1)-2,2
0073                FAKIT(J)=FAKIT(J)-PDELT
0074        302     CONTINUE
0075        301     CONTINUE
0076        305     IF(MP.EQ.0)GO TO 306
            C                   UNWRAP THE NEG DISCS
0077                DO 303 I=1,MP
0078                TDELT=TDELT+2.E0*PI
0079                DO 304 J=JRAY(I),JRAY(I+1)-2,2
0080                FAKIT(J)=FAKIT(J)+TDELT
0081        304     CONTINUE
0082        303     CONTINUE
            C                   OUTPUT A FILE FOR PLOTTING OF UNWRAPPED PHASE-1ST HALF
            C                   OF DATA ONLY.
0083        306     CALL PLTFIL(FAKIT,0,N,1)
            C                   TAKE THE SLOPE OUT OF 1ST HALF(UNWRAPPED) OF IMAG. DATA
0084                DBAS=0.5E0
0085                DBAS=SIGN(DBAS,FAKIT(N))
0086                FAZDIF=-PI*INT(FAKIT(N)/PI+DBAS)
0087                FAZINC=FAZDIF/(SN/2.E0)
0088                DO 55 I=4,N,2
0089                FI=FLOAT(I/2-1)
0090                FAKIT(I)=FAKIT(I)+FAZINC*FI
0091        55      CONTINUE
            C                   SYNTHESIZE 2ND HALF OF IMAG.DATA FROM 1ST HALF.
0092                FAKIT(N+2)=0E0
0093                DO 155 I=4,N,2
0094                FAKIT(IHN+4-I)=-FAKIT(I)
0095        155     CONTINUE
            C                   OUTPUT A FILE FOR PLOTTING OF COMPLETE DOCTORED-UP
            C                   PHASE DATA.
0096                CALL PLTFIL(FAKIT,0,N,1)
            C                   INVERSE TRANSFORM TO CEPSTRUM DOMAIN
0097                CALL FFTDP(FAKIT,N,1)
            C                   OUTPUT A FILE FOR PLOTTING OF THE RAW CEPSTRUM DATA.
0098                CALL PLTFIL(FAKIT,0,N,1)
            C                   PERFORM THE SELECTED GATING OPERATION.
0099                IF(FILT.EQ.'A')GO TO 130
0100                IF(FILT.EQ.'B')GO TO 140
0101                IF(FILT.EQ.'C')GO TO 150
0102        130     CALL COMBD(IHN,FAKIT)
0103                GO TO 160
0104        140     CALL LOWCD(IHN,FAKIT)
0105                GO TO 160
0106        150     CALL HIYCD(IHN,FAKIT)
            C                   OUTPUT A FILE FOR PLOTTING OF THE MODIFIED CEPSTRUM
0107        160     CALL PLTFIL(FAKIT,0,N,1)
            C                   SCALE THE TRANSFORMED DATA.
0108                DO 12 I=1,IHN,2
0109                FAKIT(I)=FAKIT(I)/SN
0110        12      CONTINUE
            C                   ZERO THE IMAG.PART OF CEPSTRUM-JUST TO BE SAFE.
0111                DO 52 I=2,IHN,2
0112                FAKIT(I)=0.E0
0113        52      CONTINUE
            C                   TRANSFORM BACK TO LOG SPECTRUM(FREQUENCY)
```

```
FORTRAN IV-PLUS V02-04           16:43:15     19-JAN-77              PAGE 4
PPTEST.FTN           /RO/TR:BLOCKS/WR
0114                 CALL FFTDP(FAKIT,N,-1)
        C                     RESTORE THE LINEAR PHASE COMPONENT-1ST HALF OF DATA'
0115                 DO 56 I=4,N,2
0116                 FI=FLOAT(I/2-1)
0117                 FAKIT(I)=FAKIT(I)-FAZINC*FI
0118      56         CONTINUE
        C                     SYNTHESIZE THE 2ND HALF OF IMAG.DATA
0119                 FAKIT(N+2)=0E0
0120                 DO 166 I=4,N,2
0121                 FAKIT(IHN+4-I)=-FAKIT(I)
0122      166        CONTINUE
        C                     EXPONENTIATE PHASE(ANTILOG)-THE HARD WAY.
0123                 DO 53 I=1,IHN,2
0124                 DOLG=EXP(FAKIT(I))
0125                 DANG=COS(FAKIT(I+1))
0126                 DBAS=SIN(FAKIT(I+1))
0127                 FAKIT(I)=DOLG*DANG
0128                 FAKIT(I+1)=DOLG*DBAS
0129      53         CONTINUE
        C                     REPORT THE # OF POS.&NEG.DISCONTINUITIES REMOVED IN
        C                     UNWRAPPING
0130                 WRITE(6,109)NP,MP
0131                 DO 360 I=1,IHN
        C                     RE-INVERT DATA, IF INVERTED EARLIER.
0132                 FAKIT(I)=FAKIT(I)*FAKSIG
0133      360        CONTINUE
        C                     TRANS BACK TO TIME DATA
0134                 CALL FFTDP(FAKIT,N,1)
0135                 DO 220 I=1,IHN,2
0136                 FAKIT(I)=FAKIT(I)/SN
0137      220        CONTINUE
        C                     REMOVE THE EXPONENTIAL WEIGHTING, IF ANY. THIS GETS
        C                     STICKY IN THE UPPER END OF ARRAY.
0138                 FAM=1E0/GAM
0139                 IF(GAM.EQ.1.E0)GO TO 250
0140                 DO 2 I=1,IHN,2
0141                 FAM=FAM*GAM
0142                 FAKIT(I)=FAKIT(I)/FAM
0143      2          CONTINUE
        C                     SMOOTH THE UNDERSAMPLED DATA WITH INTERPOLATION. THIS
        C                     OPERATION PLACES INTERPOLATED POINTS MIDWAY BETWEEN
        C                     DATA POINTS. REPEATS THIS OPERATION UNTIL MAX ARRAY(512)
        C                     SIZE IS REACHED.
0144      250        NTRP=SQRT(FLOAT(512/N))
0145                 DO 500 NIT=1,NTRP
0146                 DO 510 MUL=1,N-1
0147                 FKSUM=0.
0148                 SYGN=(-1)**MUL/PI
0149                 ID=-1
0150                 CUL=MUL+0.5
0151                 DO 520 I=1,N
0152                 SYGN=-SYGN
0153                 ID=ID+2
0154                 FKSUM=FKSUM+FAKIT(ID)*SYGN/(CUL-I)
0155      520        CONTINUE
0156                 FAKIT(2*MUL)=FKSUM
```

```
FORTRAN IV-PLUS V02-04            16:43:15    19-JAN-77          PAGE 5
PPTEST.FTN          /RO/TR:BLOCKS/WR
0157    510         CONTINUE
0158                N=2*N-1
0159                IF(NIT.EQ.NTRP) GO TO 500
0160                DO 530 J=1,N
0161                FAKIT(2*(N-J)+1)=FAKIT(N+1-J)
0162    530         CONTINUE
0163    500         CONTINUE
        C                   OUTPUT A FILE FOR PLOTTING OF THE SMOOTHED RECONSTRUCTED
        C                   DATA
0164                CALL PLTFUL(FAKIT,0,N,1)
0165                WRITE(6,120)
0166    11          FORMAT('$COMB(A),EARLY(B),LATE(C),SELECT FILTER: ')
0167    20          FORMAT('$FILE ')
0168    30          FORMAT(Q,30A1)
0169    34          FORMAT(A1)
0170    106         FORMAT('$INPUT NO SAMP PTS ')
0171    109         FORMAT(I4)
0172    111         FORMAT(F10.5)
0173    112         FORMAT(E10.0)
0174    119         FORMAT('$EXP. WEIGHTING FACT. ')
0175    120         FORMAT('$DONE')
0176    142         FORMAT('$NO.FILE PTS TO READ ')
0177    210         FORMAT(2X,I3,2X,2(E16.8,2X))
0178    230         FORMAT('$FOR ORIG DATA PLOT ONLY, TYPE 1 ')
0179    999         END
```

PROGRAM SECTIONS

NAME	SIZE		ATTRIBUTES
$CODE1	004444	1170	RO,I,CON,LCL
$PDATA	000034	14	RO,D,CON,LCL
$IDATA	000462	153	RW,D,CON,LCL
$VARS	011646	2515	RW,D,CON,LCL
$TEMPS	000010	4	RW,D,CON,LCL

TOTAL SPACE ALLOCATED = 017040 3856

PPTEST,PPTEST/-SP=PPTEST

A6

```
       SUBROUTINE FFTDP(DATA,NN,ISGN)
C              THIS SUBROUTINE TAKEN FROM N.M. BRENNER "THREE FORTRAN
C              PROGRAMS THAT PERFORM THE COOLEY-TUKEY FOURIER TRANSFORM"
C              MIT LINCOLN LAB TECH NOTE 1967-2
       REAL   DATA(2048),TEMPR,TEMPI,THETA,WR,WI
       N=2*NN
       J=1
       DO 5 I=1,N,2
       IF(I-J)1,2,2
1      TEMPR=DATA(J)
       TEMPI=DATA(J+1)
       DATA(J)=DATA(I)
       DATA(J+1)=DATA(I+1)
       DATA(I)=TEMPR
       DATA(I+1)=TEMPI
2      M=N/2
3      IF(J-M) 5,5,4
4      J=J-M
       M=M/2
       IF(M-2) 5,3,3
5      J=J+M
       MMAX=2
6      IF(MMAX-N) 7,9,9
7      ISTEP=2*MMAX
       DO 8 M=1,MMAX,2
       WR=FLOAT(ISGN*(M-1))
       WI=FLOAT(MMAX)
       THETA=3.14159265E0*WR/WI
       WR=COS(THETA)
       WI=SIN(THETA)
       DO 8 I=M,N,ISTEP
       J=I+MMAX
       TEMPR=WR*DATA(J)-WI*DATA(J+1)
       TEMPI=WR*DATA(J+1)+WI*DATA(J)
       DATA(J)=DATA(I)-TEMPR
       DATA(J+1)=DATA(I+1)-TEMPI
       DATA(I)=DATA(I)+TEMPR
       DATA(I+1)=DATA(I+1)+TEMPI
8      CONTINUE
       MMAX=ISTEP
       GO TO 6
9      CONTINUE
       RETURN
       END
```

L. B. POCHE, JR.

```
      SUBROUTINE LOWCD(N,HIDATA)
C              THIS SUBROUTINE PROVIDES "EARLY-PASS" GATING. IT ZEROES
C              ALL POINTS SYMMETRICALLY IN THE CEPSTRUM BETWEEN THE
C              CUTOFF POINT AND THE CENTRAL POINT INCLUDING THE CUTOFF
C              POINT.
      REAL HIDATA(N)
      WRITE(6,1)
      READ(5,2)IRLY
      DO 3 I=IRLY*2+1,N-(2*IRLY+1),2
      HIDATA(I)=0E0
3     CONTINUE
1     FORMAT('$EARLY PASS CUTOFF ')
2     FORMAT(I4)
      RETURN
      END
```

```
      SUBROUTINE HIYCD(N,HIDATA)
C              THIS SUBROUTINE PROVIDES "LATE-PASS" GATING. IT ZEROES
C              ALL POINTS SYMMETRICALLY BETWEEN THE END POINTS OF THE
C              CEPSTRUM AND THE CUTOFF POINT. DOES NOT ZERO THE CUTOFF
C              POINT.
      REAL HIDATA(N)
      WRITE(6,1)
      READ(5,2)LATE
      DO 3 I=1,LATE*2-3,2
      HIDATA(I)=0E0
3     CONTINUE
      DO 4 I=N-(LATE*2-5),N,2
      HIDATA(I)=0E0
4     CONTINUE
1     FORMAT('$LATE PASS CUTOFF ')
2     FORMAT(I4)
      RETURN
      END
```

```
      SUBROUTINE COMBD(N,HIDATA)
C             THIS SUBROUTINE GENERATES A GATING COMB FOR
C             REMOVING THE SINGLE-POINT COMPONENTS OF THE IMPULSE
C             TRAIN. "DELAY" SHOULD BE ENTERED AS THE NO. OF THE
C             FIRST POINT IN THE IMPULSE TRAIN. "INTERVAL" SHOULD BE
C             ENTERED AS THE NO. OF POINTS BETWEEN THE 1ST & 2ND &
C             SUBSEQUENT IMPULSE POINTS.  UP TO 10 SEQUENCES OR
C             IMPULSE TRAIN VALUES MAY BE ENTERED. GATED POINTS ARE
C             REPLACED BY THE MEAN VALUES OF THE NEIGHBORING
C             POINTS TWO POINTS AWAY AND ON EITHER SIDE OF THE GATED
C             POINT. STARTING-POINT SYMMETRY IS MAINTAINED AT THE ENDS
C             OF THE CEPSTRUM.
      DIMENSION IDLY(10),IDEL(10)
      REAL HIDATA(1),FK0,FK1,FK3,FK4
      BYTE IANS
      K=1
7     WRITE(6,1)
      READ(5,2) IDLY(K)
      WRITE(6,3)
      READ(5,2) IDEL(K)
      WRITE(6,4)
      READ(5,5) IANS
      IF(IANS.EQ.'N')GO TO 6
      K=K+1
      GO TO 7
6     DO 8 L=1,K
      DO 9 J=2*IDLY(L)-1,N-(2*IDLY(L)-1),2*IDEL(L)
      FK1=HIDATA(J-2)
      FK3=HIDATA(J+2)
      FK0=HIDATA(J-4)
      FK4=HIDATA(J+4)
      HIDATA(J)=(FK0-FK4)/2+FK4
9     CONTINUE
8     CONTINUE
1     FORMAT('$DELAY ')
2     FORMAT(I4)
3     FORMAT('$INTERVAL ')
4     FORMAT('$MORE? (Y OR N) ')
5     FORMAT(A1)
      RETURN
      END
```

A9

header

SUBROUTINE UF

This subroutine originally generated a 128-point time series function similar in appearance to Ulrych's seismic wavelet. It allowed keyboard inputs of echo amplitude, echo delay, and glitch amplitude. The expression used to generate the waveform was

$$UF(t) = \frac{(t - 66.5)\,(t - 41.5)\,e^{\left(81 - \frac{(t - 55.8)^2}{270}\right)}}{1155}$$

The glitch was added at the 49th point and its echo at 49 + delay.

SUBROUTINE FILRED

This is a file-reading subroutine which is used to load input data from the selected file. It contains provision for keyboard inputs which specify the number of points to be discarded at the beginning of the data sequence and the sifting factor to be employed in sampling the data. The data are loaded into the array in alternate positions corresponding to the real parts of complex numbers.

SUBROUTINE PLTFIL

This subroutine writes data from an array of complex points as an output file to a storage device in a format compatible with the general-purpose library graphics program in use at this laboratory. It provides for selection from the keyboard of real, imaginary, or magnitude data to be written to the output file.

SUBROUTINE PLTFUL

This subroutine is similar to PLTFIL except that is is designed to output from a 512-point array of real data only.